

1	2	3	4	5	6	7	8	9
161	Iv stand wheel	<ul style="list-style-type: none"> • S.S. tubular pipe. • Five legged heavy polypropylene base mounted on 5 cms castors. • Double hook S.S. adjustable IV rod with a Bakelite knob. • Knockdown construction. 	NATIONAL MEDITEK	NATOMED	EACH	2,750.00	2,100.00	Kamala Agencies L1
162	IVF LAB EQUIPMENT	<p>(A) – IVF SET-UP :1) Specification for Inverted Research Microscope for Bright field & Hoffman modulation contrast / 3D Contrast Images along with Micromanipulator & Warm Stage (ICSI UNIT)</p> <p>Microscope Body: Microscope body with Infinity optical corrected ;optical system, Mechanical tube length 200mm, Par focal distance 60mm, Extensible optical free space up to 80mm for attaching others attachment in future, facility for 3 way or more light distribution of light, up/ down focusing, left & right side port for attaching digital camera upgradeable to one additional port for another camera, binocular tube with diopter adjustment facility. Magnification changer 1.5x/2x. Condenser: Universal 7 Position condenser suitable for microscopy techniques. Illumination: Uniform High Powre i.E.D Illumination suitable for all microscopy techniques ;Eyepieces: 10X with F.O.V 22 or better with diopter adjustment facility.; Nosepiece: Sextuple revolving nosepiece.: Stage: XY Rectangular mechanical stage with Universal sample Holder. NAMC/HMC attachment NAMC/HMC condenser lens with n.a. 0.44, w.d. 44mm & contrast control polarizer, with modules. ;</p>	MICRO MAN IPULAT	EPPENDORF INDIA PVT LTD	WITH FULL LAB SETUP/ EACH	61,000,000.00	37,050,000.00	Kamala Agencies L1

1	2	3	4	5	6	7	8	8	9
162		<p>Objectives: Long working distance Objectives for Bright Field & 3D Contrast/HMC/NAMC application;</p> <ul style="list-style-type: none"> • 4X(N.A.0.10, W.D.30MM);• NAMC 10X (N.A.0.25, W.D. 6.2 MM);• NAMC 20XF (N.A.0.4, W.D.3.1 MM); • NAMC LWD 40X (N.A.0.55, W.D.2.1 MM); <p>Micromanipulator should have following specifications/features:- Drive Unit -X,Y,Z,- Movements 10mm; Control Knob: X-Y-Z-Axes Control Knob 10mm Movement ; Joy Stick Movement (X&Y) 2mm(Max.); Control Knob Movement 250um (With 2um Min. Scale). (One Rotation) MICROINJECTOR (OIL OR AIR TYPE): Movement Distance -Movement range 53mm ; Full rotation of knob 500um for oil / 6mm for Air ;Minimum Graduation 10um for oil / 120um for Air Control Value Full rotation of knob 10ul for oil / 480ul for Air ;Minimum Graduation 0.2ul for oil/ 9.6ul for Air; Syringe 1.1cc metal type for oil / 4.2cc glass type for air;WARM STAGE (GLASS TYPE HAVING 10YEARS WARRANTY ON GLASS BREAKAGE) :- PRESET TEMPERATURE : ROOM TEMP. TO 50 deg.C.; ACCURACY OF TEMP. : +/- 0.3 deg. C. INDICATION GLASS THICKNESS : 0.5MM ;THE WARM PLATE SHOULD BE CE/UI/c-UL COMPLIANT. THERE SHOULD BE A BUILT IN TEMP. CONTROL SENSOR TO ENSURE EXCELLENT HEAT CONDUCTIVITY.</p>							


1	2	3	4	5	6	7	8	8	9
162	THE CONTROLLER SHOULD BE PAD CONTROL ADOPTED FOR THE THERMOPLATE AND SHOULD PROVIDE IDEAL TEMP. CONTROL, MINIMIZES OVERSHOOT AND IS SHOULD HAVE AUTO CUT OPTION (INTERNAL) FOR TEMP. CONTROL ; CCTV ATTACHMENT:- 24" LED TV MONITOR WITH CCTV COLOR CAMREA ; 1) Specification for Upright Binocular Microscope for Bright Field, Phase Contrast Microscopy Application ; Optical System: Infinity corrected Optical system. Eyepiece Tube: Binocular Tube with 30° inclination or better. Interpupillary Distance :47-75mm, Eyepiece: 10X paired eyepiece with 20mm F.O.V. with Dioptric adjustment facility on Both Eyes- Illumination: Uniform LED illuminator having Fly-eye lens design with working life more than 50,000hrs (must mention in Technical Catalogue for verification). Nosepiece: Inward Quadruple nosepiece to accommodate 4 objectives at a time	(SS) Standard Features: • Frame work made of stainless steel tubular pipe of 2.5 cms. Dia. Mounted on four 7.5 cms. Castors. • Two fixed S.S. shelves of heavy gauge with railings • Knockdown construction. Size: 68 L x 45 W x 82 H cms	Newtek Instruments	Newtek	Each	15,900.00	9,500.00	National Enterprisers	21/08/2019
164	Instruments trolley with wheel								✓ 21/08/2019


1	2	3	4	5	6	7	8	8	9
166		Cooled CCD digital camera, CCD Sensor 1/2" Light-Sensitive Pixels, 3.3 million real pixels; 2048 x 1536, Binning Modes 2x2, 3x3, 4x4 in full colour, pixel Size : 3.45µm x 3.45µm, Digital Output 10 bits, Readout Frequency 20, 10, 5, 2.5MHz, Frame Rate : 30fps full field of view (higher fps with ROI functions) camera. Image analysis software should have acquisition and device control, filter for image enhancement, background and dark field correction, region and line measurement, autocalibration, image annotation, live histogram, gamma correction. Branded computer including Intel Core™ i3, 4GB RAM, 500 GB hard disk, DVD-RW, Windows® 8.1, 24" LED/TFT Monitor with 1 KV UPS, ISO / CE conformity certification. Bidders must submit the sole / exclusive distributor certificate issued by the manufacturer along with relevant catalogues. Warranty: two years.	NATIONAL MEDITEK NATOMED	8" EACH	390.00	250.00	Kamala Agencies	L1	
168	Kidney Tray	6" & 8" SS	NATIONAL MEDITEK NATOMED	6" EACH	410.00	250.00	Kamala Agencies	L1	
168	Kidney Tray	6" & 8" SS	Cybowl vet urine strips for 10 parameters (Uro, Glu, Bil, Ket, SG, Bld,pH, Pro, Nit,& Leu) specific gravity (for specific gravity we advise to use our refractometers).	CYBOW	50 STRIP	3,072.00	1,920.00	Kamala Agencies	L1
169	Krulab Test Strips	Cybowl vet urine strips for 10 parameters (Uro, Glu, Bil, Ket, SG, Bld,pH, Pro, Nit,& Leu) specific gravity (for specific gravity we advise to use our refractometers).	CYBOW	CYBOW	100 STRIP	4,224.00	2,640.00	Kamala Agencies	L1


1	2	3	4	5	6	7	8	9
170	Laboratory instruments set	Set of instruments and equipment for laboratory use.	Himedia Laboratories Pvt Ltd	HiMedia Each	1,574.00	1,200.00	National Enterpriser L1 \$	
171	Laparoscope for sterilization small animal	CDD CAMERA WITH COUPLER& HAED model : F1156.06 ENDOSCOPE FUNCTION KEY PROVIDESTHE ANDIOSCOPY TYPE SETTING, OPTIMUM ADJUSTING OF ILLUMINATION WITH SMALL MEDIUM /LARGE ENDOSCOPE,,WHITE BALANCE,DIGITAL ANTI-MOIRE FUNCTION,ILLMINATED FUNCTIONS	SAKET SURGICALS PVT LTD	SSAM // EACH	1,510.00.00	1,050.00.00	Kamala Agencies L1	
172	large animal FETATOMY SET	Large animal fetotomy set with accessories High quality imported fetotomy set containing 1. inde'sembryotomy knife (stainless steel 5" L. with one large finger ring and handle) Guenther's embryotomy knife with two fingers (stainless steel 2 and half" L) Obstetrical Saw wire (rapid cutting, rust resistant, 27 braided filaments 10 meter long with a provision to keep unused wire in a plastic dispenser pack) Thygesen'sfetotomy. (Two tube model with adjustable handle for obstetrical chain with insertion coil and cleaning brush 33" L.) Bovine cervical forceps Fetatomc case (Vinyl case with individual posckets for obstetrical handles, wire saw, chains and other obstetrical equipment)	Newtek Instruments	Newtek Each	33.420.00	21,700.00	National Enterpriser L1 \$	
173	Lead gloves ,Goggles & Approval	NATIONAL MEDITEK	NATOMED EACH	2,890.00	1,600.00	Kamala Agencies L1		


1	2	3	4	5	6	7	8	9
174	Littmann stethoscope	A luxury model stethoscope. Known for its great quality and sound. Floating diaphragm enables listening to high and low frequency sounds by changing the pressure on the diaphragm.	LITTMAN	LITTMAN	EACH	9,200.00	5,800.00	Kamala Agencies L1
175	Laminar Air flow unit having SS body and wheels	Length 5-8 feet ,4-5 feet width, a)Prefilter - 95% efficient at 5 microns, b)HEPA filter-99.9% efficient at 0.3 microns, c)Air velocity-90 ft./minute(0.45m/sec +20% at rated pressure drop, d)Operating filter resistance - maximum 32 mm WG, e)Fan-double inlet, centrifugal,super silent, f)Manometer and pressure gauge indicator, g)Lighting-800 lux minimum at work surface, h)Stainless steel work tops with gas taps/ vacuum points, i)U V light facility, j)Structure - Steel Body, clear perspex side screen with front sliding panel,overall length-1200 to 1900 m	P.L. TANDON & CO	TANCO	MODEL, PLT273/ EACH	342,000.00	220,000.00	Kamala Agencies L1
176	laryngoscope	Battery handel,throat cannula,with 2 attachment for Anesthesia.	NATIONAL MEDITEK	NATOMED	EACH	6,786.00	2,390.00	Kamala Agencies L1
177	Liquid Nitrogen container	Capacity 45-50 liters of Liquid Nitrogen with static evaporation loss rate of 0.38 liters per day at SIP, 11 canisters with OD 72mm, height 280mm. The level of liquid nitrogen from bottom should be about 42 cms. The neck diameter should be 120 mm. This container is required for storage and transport of FS doses from production centre to district quarters. More than 99% pure. Each bottle will have 2.5 lit AR/Excellar	IMV INDIA PVT LTD	IMV, MODEL: GT40 (Made in France)	EACH	53,480.00	38,200.00	Kamala Agencies L1


1	2	3	4	5	6	7	8	9
178	Liquid Nitrogen Pressurized Dewar LN2 stored with hose pipe	capacity 180-200Ltr. Liquid Nitrogen with SS body and wheels along with hose pipe.	Inox	Inox	200 Ltr	394,800.00	282,000.00	National Enterpriser L1 s
179	Liquid Nitrogen transfer hose pipe	Fabricated from stainless steel with a highly flexible outer spiral wrap, all ends are polished to a high luster finish, multiple layer super insulation for lowest possible heat loss, it should be single hinge, or double hinge, Length-10 feet.	IMV INDIA PVT LTD	CRYOPAL / CRYO DIFFUSION, (MADE IN FRANCE)	EACH	44,900.00	21,600.00	Kamala Agencies L1
























1	2	3	4	5	6	7	8	9	
1	2	Interior Size: 4 ft / 1.2 m; Interior walls and removable work table must be of corrosion resistant stainless steel, with side glass wall. • It should have antimicrobial coating on cabinet walls to minimize contamination. • Dynamic chamber plenum with negative pressure surrounding contaminated positive pressure plenum. • LCD display should preferably be present to check the remaining filter life. • Dual, long life ULPA or equivalent filter (cleanliness class 99.999% at 0.1 micron to 0.3 micron size particles. Air flow ratio of A2 (B1) type (approximately 65% / 35%). Microprocessor controlled alarming systems for supervision of all cabinet functions. Visual and audible alarms while the height exceeds • Alarms for low air exhaust, low air velocity of inner laminar flow, fault of inflow and exhaust fans. Actual work opening height approximately 25mm larger than sash opening. Frameless, shatterproof sash with automatic UV shut-off on • sash opening. Raised armrest design and airflow grille-side-capture zones and negative pressure side walls. Fluorescent light intensity ≥900 Lux. • Germicidal UV lamp ($\geq 30\text{mW/cm}^2$ of 254 nm), 2 choke-less fluorescent lamps, one service fixer for gas inlet, 2 electrical sockets. • User friendly long work type	180 CO2 INCUBATOR (CLASS 11 A2)	EPPENDORF INDIA PVT LTD	EPPENDORF / CELIXPERT C170	L1 Kamala Agencies	1,215,000.00	1,995,000.00	9

20710
2.1 151115

2019.08.26

1	2	3	4	5	6	7	8	9
		Built-in high efficiency ECM centrifugal blower with long life brushless blower motor. DC motor/magnetic motor of high torque• made of the latest technology and consumes less energy, generates less heat, noise level should be less than 65 decibels (dBA). Supplied with supporting base. Standard compliance of EN 12469, ISO 14664.1 class 3, IEST-GCC1001, IEST G-CC1002 for air cleanliness and electrical safety. • System should have RS-Port. • This system in combo with CO ₂ Incubator. Direct heat and air jacketed design. • Temperature control : ambient + 3°C to 60°C; Temp. Uniformity, °C : < ± 0.20 C, Temp. Controllability, °C : < ± 0.10C, 150-170 Litre Capacity. Forced convection designs. • ULPA filtration for inflow air. 8 heaters, grouped into 3 zones. • Should have CO ₂ control range from 0-20% with accuracy and uniformity of ±0.1% and equipped with rapid recovery system to maintain the CO ₂ concentration after door opening without overshoot. Unique HPA validated quadruple contamination control contains ULPA filter, UV Lamp. • 90°C wet heat overnight decontamination cycle; external surfaces are covered with antimicrobial coating. • Corrosion resistant full stainless steel interior.	180					

2.11.2019

21.08.2019

21.08.2019
29.08.2019
29.08.2019
29.08.2019

1	2	3	4	5	6	7	8	8	9
180		<ul style="list-style-type: none"> RS-Port facility which can be used for data logging, when required. IR Sensors with on-screen quick help microprocessor with alarms (temp low/high, CO₂ low/high, door open, Humidity change, etc.) Interactive LCD screen for changing alarm settings, diagnostic interface; password protection; error logging. Non-volatile memory which must guarantee the data integrity regardless of length of time or frequency of power interruption. Air-tight seal door system with inner glass door. One 30 Kg CO₂ cylinder and one regulator. Suitable UPS with battery for power backup. Split AC of 1.5 ton (at least 3 Star) to maintain temperature with stabilizer. The equipment should have three year warranty on site after installation of the facility. The equipment should be equipped with heavy duty burst resistant electrical wires & sockets. Should be provided with prompt service (24hrs) on call basis. 							
181	MASTITIS DETECTOR		<p>A) Draminski mastitis detector with 1 cup with reading for 1 quarter (Cat. No: MD4Q)</p> <p>C) Draminski mastitis with 4 cups with reading for 4 quarter (CAT NO: MD4 X 4Q)</p> <p>B) Draminski mastitis detector with 1 cup with reading for 4 quarter (CAT. No : MD4Q)</p>	DRAMINSKI	1 QTR EACH	52,900.00	28,000.00	Kamala Agencies	L.I

1	2	3	4	5	6	7	8	9
181	MASTITIS DETECTOR	A) Draminski mastitis detector with 1 cup with reading for 1 quarter (Cat. NO: MD4Q) C) Draminski mastitis with 4 cups with reading for 4 quarter (CAT.NO: MD4 X 4Q) B) Draminski mastitis detector with 1 cup with reading for 4 quarter (CAT. No : MD4Q)	DRAMNISKI	DRAMNISKI	4 QTR EACH	78,100.00	46,000.00	Kamala Agencies L1
181	MASTITIS DETECTOR	A) Draminski mastitis detector with 1 cup with reading for 1 quarter (Cat. NO: MD4Q) C) Draminski mastitis with 4 cups with reading for 4 quarter (CAT.NO: MD4 X 4Q) B) Draminski mastitis detector with 1 cup with reading for 4 quarter (CAT. No : MD4Q)	DRAMNISKI	DRAMNISKI	2 QTR WITH 4 CUP EACH	105,100.00	58,000.00	Kamala Agencies L1
182	Mastix Kit	Masti padel, dispersion&mastis also. Solution 500ml along with instruction manual.	NATIONAL MEDITEK	NATOMED	2 KIT UNIT	1,378.00	1,190.00	Kamala Agencies L1
184	SCISSORS(6",8" STRAIGHT	Stainless steel, straight, 6" & 8" long	NATIONAL MEDITEK	NATOMED	6" STRAIG HT	532.00	340.00	Kamala Agencies L1
184	SCISSORS(6",8" CURVED)	Stainless steel, straight, 6" & 8" long	NATIONAL MEDITEK	NATOMED	8" STRAIG HT	532.00	340.00	Kamala Agencies L1
185	SCISSORS(6",8" CURVED)	Stainless steel, curved, 6" & 8" long	NATIONAL MEDITEK	NATOMED	6" CURVE D	532.00	290.00	Kamala Agencies L1
185	SCISSORS(6",8" CURVED)	Stainless steel, curved, 6" & 8" long	NATIONAL MEDITEK	NATOMED	8" CURVE D	532.00	290.00	Kamala Agencies L1

2018/19

2019

2019

1	2	3	4	5	6	7	8	9
186	Modular OT	Wall panels- 44mm ,90 sq. mt; ceiling panels 44mm ,55 sq mt.; return air risen panel with risen shrill- 4 no., partition caving - 32 rmt, wall & ceiling cutouts-27 nos, antibacterial paint 145 sq.mt; flooring for OT- 55sq.mt; floor carvings 32 rmt, with provision of washroom, including 1 No laminar air flow, 1 No portable x-ray machine, 1 no of microscope, 1 no of shadowless light,1 no metal detector, 1 no of mattress made of coir(size 10 ft * 12 ft with 18 inch thickness), 1 no of hot air oven, 1 No autoclave, 1 No incubator, 1 No sterilisation drum, 1 no of OT door sliding, 1 No of surgeon control panel along with electrical distribution board push bottom type , 1 No of pressure relief dampen , 1 No of storage unit flush with panel , 1 No of OT waiting board , 8 no of peripheral lights , X ray view box 2plates 1 hatch box 1 no, and 1 no of 15 KVA DG Set with internal electrification on turnkey basis for large and small animals	TANCO, (Wall panel, ceiling panel, clean room material Ahu from reputed manufacture from India, Civil work by Own, Laminar Flow-Tanco, Microscope- Nikon, Shadowless Light-Reputed P.I.. TANDON & CO	EACH	Kamala Agencies 1.1	4,258,000.00		

21/5/19

21/5/19


21/5/19

21/5/19

1	2	3	4	5	6	7	8	9
186	Modular OT	Wall panels- 44mm ,90 sq. mt; ceiling panels 44mm .55 sq mt.; return air risen panel with risen shrill- 4 no., partition caving - 32 rmt, wall & ceiling cutouts-27 nos, antibacterial paint 145 sq.mt.; flooring for OT- 55sq.mt; floor carvings 32 rmt, with provision of washroom, including 1 No laminar air flow, 1 No ultrasound, 1 No portable xray machine, 1 no of microscope, 1 no of shadowless light,1 no of anaesthesia machine, 1 no laproscopic device, 1 no metal detector, 1 no of mattress made of coir(size 10 ft * 12 ft with 18 inch thickness), 1 no of hot air oven, 1 No autoclave, 1 No incubator, 1 No sterilisation drum, 1 no of OT door sliding, 1 No of surgeon control panel along with electrical distribution board push bottom type , 1 No of pressure relief dampen, 1 No of storage unit flush with panel , 1 No of OT waiting board , 8 no of peripheral lights , X ray view box 2plates Hatch box 1 no, and 1 no of 15 KVA DG Set with internal electrification on turnkey basis for large and small animals	TANCO, (Wall pannel, ceiling pannel, clean room material Ahu from reputed manufacture from India, Civil work by Own, Laminar Flow-Tanco, Microscope- Nikon, Shadowless Light-Reputed Make, Metal Detector, Nationed, Coil Mattress- From Reputed Make, Hot Air Oven- Tanco,	EACH	10,562,000.00	6,200,000.00	Kamala Agencies L1	
187	Mosquito artery forceps 4"(straight,ss)	NATIONAL MEDITEK	NATOMED	EACH	430.00	320.00	Kamala Agencies L1	

1	2	3	4	5	6	7	8	9
188	Mosquito artery forceps 4"(Curved,ss)	4"(Curved,SS)	NATIONAL MEDITEK	NATOMED EACH	510.00	370.00	Kamala Agencies L1	
189	Milking Gloves, Nitrile	Used by farmers worldwide. Extra strong nitrile examination glove. Used as a milking glove.	NATIONAL MEDITEK	NATOMED EACH	350.00	1.80	Kamala Agencies L1	
190	Microtips with Box	Polypropylene. Sterile (200-1000 micro litre) with box	Himedia Laboratories Pvt Ltd	HiMedia Micro Ltr/Each	200 602.00	490.00	National Enterpriser L1 s	
190	Microtips with Box	Polypropylene. Sterile (200-1000 micro litre) with box	Himedia Laboratories Pvt Ltd	HiMedia 1000Micro Ltr/Each	885.00	720.00	National Enterpriser L1 s	
191	Medical Refrigerator	Different Type 99 ltr- 110,310-1950,-225	SM Scientific Instruments Pvt Ltd	JINDAL, LTR/ EACH	150,000.00	85,000.00	National Enterpriser L1 s	
191	Medical Refrigerator	Different Type 99 ltr- 110,310-1950,-225	SM Scientific Instruments Pvt Ltd	JINDAL, LTR/ EACH	300	190,000.00	National Enterpriser L1 s	
191	Medical Refrigerator	Different Type 99 ltr- 110,310-1950,-225	SM Scientific Instruments Pvt Ltd	JINDAL, LTR/ EACH	400	220,000.00	National Enterpriser L1 s	
191	Medical Refrigerator	Different Type 99 ltr- 110,310-1950,-225	SM Scientific Instruments Pvt Ltd	JINDAL, LTR/ EACH	500	485,000.00	National Enterpriser L1 s	

1	2	3	4	5	6	7	8	9
192	Medicine cabinet	<ul style="list-style-type: none"> • Size: 1800mm ht x 900 mm width. • Epoxy coated mild steel framework. <p>Cabinet has two lockable upper doors with glass panes, double doors in the lower section, three adjustable glass shelves in the upper section, and one removable. Non-adjustable metal shelf in the lower section.</p>	SM Scientific Instruments Pvt Ltd	JINDAL	Each	56,200.00	38,000.00	National Enterprisers L1
193	Metal Detector	For Bovine	NATIONAL MEDITEK	NATOMED	EACH	139,800.00	88,000.00	Kanala Agencies L1
194	Mouth gag	For dog, small & large ruminants SS	NATIONAL MEDITEK	NATOMED	EACH	1,150.00	700.00	Kanala Agencies L1



21.08.2019

✓ 100%
✓ 100%
✓ 100%

1	2	3	4	5	6	7	8	8	9
		<p>Special Features:</p> <p>Digital single set point temperature</p> <p>Ceramic wool insulation permits faster heat up, reducing energy consumption.</p> <p>Door safety switch stops power to heating elements when door is opened.</p> <p>Equipped with thermocouple break protection, that helps preventing thermocouple failure runway condition.</p> <p>Technical Specification:</p> <p>Material of Construction:</p> <p>Light weight with ceramic wool insulation(instead of Brick insulation).</p> <p>The outer casting is made of double walled thick PCRC sheet, duly painted with attractive stove enamel.</p> <p>Heating elements are made of A-1 wire and backed by high temperature ceramic wool insulation, which avoids loss of energy.</p> <p>The temperature control unit consists of Energy regulator, fitted in front of the furnace with two pilot lamps.</p> <p>The apparatus is complete with one pyrometer, thermocouple, silver thermal fuse, and main lead with power plug. To work on 220/230 Volts AC or 400/440 Volts AC.</p> <p>Working Temperature: 1000 deg C; Maximum Temperature: 1100 deg C; Heating Element: A1 Wire</p>							
196	Muffle furnace(inner size-150 x 150 x300mm)	SM Scientific Instruments Pvt Ltd	JINDAL	Each	53,200.00	38,000.00	National Enterprisers	Ltd	
197	Micro pipette large (electronic digital)	EPPENDORF INDIA PVT LTD	EACH	136,800.00	89,260.63	Kamala Agencies	Ltd		

1	2	3	4	5	6	7	8	9
198 Micro pipette medium(electronic digital)	Operational characteristics 1) Adjustable Volume 20-200 µl. 2) Precision up to 2%. 3) Accuracy up to 1%. 4) Fully autoclavable 5) Provided with automatic tip-eject feature 6) Able to use with one-hand only	EPPENDORF INDIA PVT LTD	EPPENDORF INDIA PVT LTD	EACH	136,800.00	89,260.00	Kamala Agencies	L1
199 Micro pipette Multichannel(electro- nic digital /stepper)	Operational characteristics 1) Adjustable Volume 20-200 µl. 2) Precision up to 2%. 3) Accuracy up to 1%. 4) Fully autoclavable 5) Provided with automatic tip-eject feature 6) Able to use with one-hand only	EPPENDORF INDIA PVT LTD	EPPENDORF INDIA PVT LTD	EACH	198,500.00	119,000.00	Kamala Agencies	L1
200 Micro pipette,Small (electronic digital)	Operational characteristics 1) Adjustable Volume 20-200 µl. 2) Precision up to 2%. 3) Accuracy up to 1%. 4) Fully autoclavable 5) Provided with automatic tip-eject feature 6) Able to use with one-hand only	EPPENDORF INDIA PVT LTD	EPPENDORF INDIA PVT LTD	EACH	140,000.00	90,000.00	Kamala Agencies	L1

2115109

July 2019

1	2	3	4	5	6	7	8	9
201	Micro Centrifuge	<p>Compact centrifuge of Max speed up to 14500 rpm with rcf 14100xg</p> <ol style="list-style-type: none"> Digital display for easy setting Rotor for 12 X 1.5, 2ml tubes Brushless motor Autoclavable rotors Separate short spin key Automatic lid opening at the end of the run to prevent sample warming Speed can be set in rpm & rcf Timer: 15 sec to 99 minutes with continuous function. Low sample heating Noise level: <52 dB(A) Power consumption: 85 W Acceleration and deceleration in 13 seconds Conforms to IEC Safety Standards Dimensions: (WxDxH) = 23x 24x13 cm Power requirement: 230V/50-60Hz <p>Rotors</p> <ul style="list-style-type: none"> 12x 1.5/2ml tube at speed 14500 rpm with rcf 14100xg Adaptor for 0.2ml PCR tubes 	<p>EPPENDORF INDIA PVT LTD</p> <p>MINISPIN PL.US</p> <p>EACH</p> <p>L1</p>	<p>Kamala Agencies</p> <p>145,000.00</p>				

✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓

✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓

✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓

✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓

1	2	3	4	5	6	7	8	8	9
202	Microscope	<p>Electrical characteristics 1) A 120V, 60Hz mono-phase electrical source with line connection plug NEMA 5-15 type. 2) Protections against over-voltage and over-current line conditions. 3) Compliance with applicable Iaitian standards and regulations. Operational characteristics 4) Binocular standard optical system biological microscope 5) Observation methods: brightfield, darkfield, and phase contrast 6) Adjustable inter-pupil distance. 7) Ocular tubes with adjustable focus. 8) Wide-field eyepieces at least 10x and 15x. 9) At least the following plan achromatic objectives provided: 4x, 10x, 40x , up to 100x (oil immersion). 10) Mechanical revolving nose piece with not less than 4 slots for interchangeable objectives positioning. 11) Integrated illumination system with a 30 W halogen lamp with adjustable light intensity or a light-limiting diode (LED). 12) Coaxial focusing system with macro and micro movements. 13) Rack-less mechanical rectangular stage with horizontal movements in both two, x and y, perpendicular directions 14) Stage provided with easy removable pincers. 15) Equipment provided with interface to attach a digital camera (optional). 16) At least one interface for printer and PC connection for data printing and transmission (optional). Additional consumables and accessories to be included in the bid price: 17) Dust cover and hard box. 18) At least n° 1 spare halogen bulb if LED is not provided 19) Complete with the necessary start up kit of consumables and reagents for initial testing, calibration and training activities</p>	NIKON	EACH	165,000.00	92,000.00	Kamala Agencies	L.I	